LOC/DME I-CZH	APP CRS	Rwy Ldg 7701
110.5	137°	TDZE 27
Chan 42		Apt Elev 30

ILS Y or LOC Y RWY 14

JACKSONVILLE INTL (JAX)


RADAR required for procedure entry. DME or RADAR required.


Rwy 14 helicopter visibility reduction below ¾ SM NA. Autopilot coupled approach NA below 750 feet MSL. For inop ALS, increase S-LOC 14 Cats A/B visibility to 1 SM. KUYER fix minimums: for inop ALS, increase S-LOC 14 all Cats visibility to 1 SM.

MALSR

MISSED APPROACH: Climb to 3000 direct CRG VORTAC and hold.


D-ATIS	JACKSONVILLE APP CON	JACKSONVILLE TOWER	GND CON
125.85	119.0 269.9	118.3 317.7	121.9 348.6





CATEGORY	A	B	C	D
S-ILS 14	306-¾ 279 (300-¾)			
S-LOC 14	480-¾ 453 (500-¾)		480-⅞ 453 (500-⅞)	
CIRCLING	520-1 490 (500-1)		600-1½ 570 (600-1½)	600-2 570 (600-2)
KUYER FIX MINIMUMS (DME REQUIRED)				
S-LOC 14	380-¾ 353 (400-¾)			
CIRCLING	520-1 490 (500-1)		600-1½ 570 (600-1½)	600-2 570 (600-2)

ELEV 30 TDZE 27



REIL Rwy 32
TDZL/RCLS Rwys 8, 14, and 26
HIRL Rwys 8-26 and 14-32

FAF to MAP 5.1 NM

Knots	60	90	120	150	180
Min:Sec	5:06	3:24	2:33	2:02	1:42

SE-3, 29 OCT 2026 to 26 NOV 2026
SE-3, 29 OCT 2026 to 26 NOV 2026