RNAV (RNP) Y RWY 14

JACKSONVILLE INTL (JAX)

APP CRS	Rwy Ldg	7701
137°	TDZE	27
	Apt Elev	29

RNP AR APCH - GPS.

For uncompensated Baro-VNAV systems, procedure NA below -5°C or above 54°C. GPS required. For inop MALSR, increase RNP 0.30 all Cats visibility to 1⅛ mile.

MALSR

MISSED APPROACH: Climb to 500 then climbing left turn to 2000 direct YEJWO and hold.

D-ATIS	JACKSONVILLE APP CON	JACKSONVILLE TOWER	GND CON
125.85	119.0 269.9	118.3 317.7	121.9 348.6

MISSED APCH FIX

4 NM

077°

257°

YEJWO

(IF) DEDDA 3000 (RF REQD)

2100 226° (3.1)

PENSE

(IF) ORTAR 3000

1800 136° (4.8)

1100 (5.5)

(IF) DIPDE 3000 Max 210K (RNP 0.70) (RF REQD)

AMLIA

1100 136° (3)

1500 100° (5.2)

1500 (2.6)

JOVFE

(FAF) NARDE

1100 (1.5)

137° (3.2)

134±

RW14

AHMIV

2300 (2)

KRISO

2300 033° (6)

2900 344° (3.6)

(IF) KAYEM 4000 Max 210K (RNP 0.70) (RF REQD) (RADAR REQD)

(IF) EYLND 4000 Max 210K (RNP 0.70) (RF REQD)

MSA RW14 25 NM

2700

ELEV 29 TDZE 27

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).

500 2000 YEJWO

NARDE

1100

1100

137°

RW14

GP 3.00° TCH 54

See planview for multiple IF locations.

3.2 NM

CATEGORY	A	B	C	D
RNP 0.30 DA	389-1	362 (400-1)		

AUTHORIZATION REQUIRED

137°

10000 X 150

26

8

TWR

7701 X 150

32

REIL Rwy 32

TDZL/RCLS Rwys 8, 14, and 26

HIRL Rwys 8-26 and 14-32

SE-3, 29 OCT 2026 to 26 NOV 2026

SE-3, 29 OCT 2026 to 26 NOV 2026