RNAV (GPS) RWY 5

MOORE-MURRELL (MOR)

WAAS	APP CRS	Rwy Ldg	5718
CH 78321	053°	TDZE	1313
W05A		Apt Elev	1313

RNP APCH - GPS.

VDP NA when using TYS altimeter setting. When local altimeter setting not received, use TYS altimeter setting and increase all MDAs 140 feet, increase LP and LNAV Cats C/D visibility ⅜ SM, increase Circling Cat B and C visibility ½ SM.

MISSED APPROACH: Climb to 2000 then climbing right turn to 4200 direct YURSU and hold.

AWOS-3	KNOXVILLE APP CON	UNICOM
126.725	132.8 360.8	122.8 (CTAF) L

Procedure NA for arrival at TAMPI on V517 northwest bound and V466-519 northeast bound.

TAMPI

4200 220° (11)

1523

RW05

(FAF) SIQCU

3200 053° (6.3)

(IF/IAF) YURSU

053° 233°

HOLD 6000 4200

5 NM

MSA RW05 25 NM

7900

4200 NoPT 009° (10.7)

(IAF) AUBRY

Procedure NA for arrival at AUBRY on V136 eastbound.

5 NM Holding Pattern

6000 4200

233° 053°

YURSU

053°

SIQCU

1.3 NM to RW05

3200

3.00° TCH 39

RW05

6.3 NM 4.5 NM 1.3 NM

2000	4200	YURSU
↑	↱	✧

ELEV 1313 TDZE 1313

0.7% UP

5718 X 100

23

5

053°

CATEGORY	A	B	C	D
LP MDA	1760-1 447 (500-1)		1760-1⅜ 447 (500-1⅜)	
LNAV MDA	1780-1 467 (500-1)		1780-1⅜ 467 (500-1⅜)	
CIRCLING	1880-1 567 (600-1)	2020-1 707 (800-1)	2160-2½ 847 (900-2½)	2420-3 1107 (1200-3)

REIL Rwys 5 and 23 L

MIRL Rwy 5-23 L

SE-1, 29 OCT 2026 to 26 NOV 2026

SE-1, 29 OCT 2026 to 26 NOV 2026